

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) An audio user-interfacing method in which items are represented in an audio field by corresponding synthesized sound sources from where sounds related to the items appear to emanate, the method including the steps of:

(a) allocating the sound sources to groups ~~of at least one~~ such that each group comprises multiple sound sourcee; sources; and

(b) ~~un-muting automatically and cyclically changing the audibility of the sound sources such as to un-mute the sound sources of each group~~ of sound sources in turn for a limited period with the ~~sound sources of the groups other than the un-muted group being at least partially muted~~ by automatically and cyclically changing the audibility of the sound sources of a particular group.

2. (Currently Amended) A method according to claim 1, wherein the sound sources are grouped allocated to the groups according to at least one characteristic of their respective associated items.

3. (Currently Amended) A method according to claim 1, wherein the sound sources are ~~grouped~~ allocated to the groups according to their positions in the audio field.

4. (Currently Amended) A method according to claim 1, wherein the sound sources are ~~grouped~~ allocated to the groups by a user.

5. (Original) A method according to claim 1, wherein each sound source has its own respective group.

B
Cont
6. (Currently Amended) A method according to claim 1, ~~wherein~~ further including un-
muting at least one group of sound sources that is treated as an exception ~~and is left un-muted~~.

7. (Currently Amended) A method according to claim 1, ~~wherein~~ further including
adjusting, by a user, the duration of said limited period ~~is adjustable by a user~~.

8. (Currently Amended) A method according to claim 1, ~~wherein~~ further including cross
fading the group whose limited period of being un-muted is ending ~~is cross-faded~~ with the group
whose period of being un-muted is next to occur.

9. (Currently Amended) A method according to claim 1, wherein each group is
associated with a respective audio-field reference relative to which the sound sources of the
group are positioned, independently moving the audio-field references ~~being independently~~
~~movable~~ relative to a presentation reference which is determined by a mounting configuration of

audio output devices used to synthesise said sound sources.

10. (Currently Amended) A method according to ~~any one of the preceding claims,~~
~~wherein claim 1 further including stabilizing~~ the audio field ~~is stabilised~~ relative to one of:

- a user's head;
- a user's body;
- a vehicle in which the user is travelling;
- the world;

B
Cont
~~this stabilisation performing the stabilization, as appropriate, in response to rotation of the user's head or body, or turning of the vehicle, taking account of whether audio output devices used to synthesise the sound sources are world, vehicle, body or head mounted, and, as appropriate, rotation of the user's head or body, or turning of the vehicle.~~

11. (Currently Amended) A method according to claim 1, wherein at least some of the said items represented by the sound sources are audio labels for services, the method further ~~involving~~ including selecting a service by selecting the corresponding audio-label sound source.

12. (Currently Amended) Apparatus for providing an audio user interface in which items are represented in an audio field by corresponding synthesized sound sources from where sounds related to the items appear to emanate, the apparatus comprising:

- storage means for storing data concerning the sound sources, this data including grouping data associating sound sources ~~[[in]]~~ into groups of at least one, each with multiple sound ~~source~~ sources;

- B
Cont
- rendering-position determining means for determining, for each of said sound source ~~sources~~, an associated rendering position at which the sound source is to be synthesized to sound in the audio field;
 - audibility-determining means for determining the audibility of each sound source based on its group, the audibility-determining means being ~~operative~~ arranged to automatically and cyclically change the audibility of the sound sources ~~such as to un-mute the~~ for un-muting each group of sound sources ~~of each group~~ in turn for a limited period with the ~~sound sources~~ of the groups other than the un-muted group being at least partially muted; and
 - rendering means, including audio output devices, for generating an audio field in which said sound sources are synthesized at their associated rendering positions and with audibility as determined by said audibility-determining means.

13. (Original) Apparatus according to claim 12, further comprising means for automatically grouping the sound sources according to at least one characteristic of their respective associated items.

14. (Original) Apparatus according to claim 12, further comprising means for automatically grouping the sound sources according to their positions in the audio field

15. (Original) Apparatus according to claim 12, further comprising a user input arrangement for enabling a user to allocate the sound sources to groups.

16. (Original) Apparatus according to claim 12, wherein each sound source has its own respective group.

17. (Original) Apparatus according to claim 12, further comprising a user input arrangement for enabling a user to adjust the duration of said limited period.

B
Cont
18. (Original) Apparatus according to claim 12, wherein the audibility-determining means includes cross-fade means for cross fading the sound sources of the group whose limited period of being un-muted is ending with the sound sources of the group whose period of being un-muted is next to occur.

19. (Currently Amended) Apparatus according to claim 12, wherein the rendering-position determining means comprises:

- means for setting the location of each of said sound ~~source~~ sources relative to an audio-field reference;
- means for controlling an offset between the audio field reference and a presentation reference, the presentation reference being determined by a mounting configuration of the audio output devices; and
- means for deriving the rendering position of each sound source based on the location of the sound source in the audio field and said offset.

20. (Original) Apparatus according to claim 19, wherein the said means for setting an offset between the audio field reference and a presentation reference, comprises user input means

for enabling a user to change said offset, and stabilisation means for varying the said offset such as to stabilise the audio field reference relative to one of:

- a user's head;
- a user's body;
- a vehicle mounting the apparatus;
- the world.

B
cont
21. (Original) Apparatus according to claim 12, wherein at least some of the said items represented by the sound sources are audio labels for services, the apparatus including a selection arrangement for selecting a service by selecting the corresponding audio-label sound source.

22. (Currently Amended) Apparatus for providing an audio user interface in which items are represented in an audio field by corresponding synthesized sound sources from where sounds related to the items appear to emanate, the apparatus comprising:

- a data store for storing data concerning the sound sources, this data including grouping data associating sound sources in groups of ~~at least one~~ multiple sound sources;
- a rendering-position determining arrangement ~~operative~~ arranged to determine, for each said sound source, an associated rendering position at which the sound source is to be synthesized to sound in the audio field;
- an audibility-determining arrangement ~~operative~~ arranged to determine the audibility of each sound source based on its group, the audibility-determining arrangement being further ~~operative~~ arranged to automatically and cyclically change the audibility of the sound sources such as to un-mute ~~[[the]]~~ each group of sound sources ~~of each group~~ in turn for a limited

period with the ~~sound sources of the~~ groups other than the un-muted group being at least partially muted; and

- a rendering subsystem, including audio output devices, arranged to generate an audio field in which said sound sources are synthesized at their associated rendering positions and with audibility as determined by said audibility-determining arrangement.

B
Cont
23. (Currently Amended) Apparatus according to claim 22, further comprising an arrangement ~~operative~~ arranged to automatically group the sound sources according to at least one characteristic of their respective associated items.

24. (Currently Amended) Apparatus according to claim 22, further comprising an arrangement ~~operative~~ arranged to automatically group the sound sources according to their positions in the audio field

25. (Original) Apparatus according to claim 22, further comprising a user input arrangement for enabling a user to allocate the sound sources to groups.

26. (Original) Apparatus according to claim 22, wherein each sound source has its own respective group.

27. (Original) Apparatus according to claim 22, further comprising a user input arrangement for enabling a user to adjust the duration of said limited period.

28. (Original) Apparatus according to claim 22, wherein the audibility- arrangement includes a cross-fader arranged to cross fade the sound sources of the group whose limited period of being un-muted is ending with the sound sources of the group whose period of being un-muted is next to occur.

29. (Currently Amended) Apparatus according to claim 22, wherein the rendering-position determining arrangement comprises:

- B
cont
- a setting arrangement for setting the location of each said sound source relative to an audio-field reference;
 - a control arrangement for controlling an offset between the audio field reference and a presentation reference, the presentation reference being determined by a mounting configuration of the audio output devices; and
 - a deriving arrangement ~~operative~~ arranged to derive the rendering position of each sound source based on the location of the sound source in the audio field and said offset.

30. (Currently Amended) Apparatus according to claim 29, wherein the said setting arrangement comprises a user input arrangement for enabling a user to change said offset, and a stabilisation arrangement ~~operative~~ arranged to vary the said offset such as to stabilise the audio field reference relative to one of:

- a user's head;
- a user's body;
- a vehicle mounting the apparatus;
- the world.

B
cont
31. (Original) Apparatus according to claim 22, wherein at least some of the said items represented by the sound sources are audio labels for services, the apparatus including a selection arrangement for selecting a service by selecting the corresponding audio-label sound source.
